

Dividing Protective Curtain DPC Fire Retardant Clear Vinyl

PRODUCT DESCRIPTION

Americover's New Fire Retardant Vinyl Covering is ideal for creating desk top and hanging barriers in hospitals, salons, schools, restaurants, offices, anywhere separation is needed.

This 12 mil heavy duty film can be glued together to create multiple widths - the roll width is 4.5′. Using vinyl glue or tape you can create wider curtains. [8′11″, 13.3′, 17.71′, 22.13′, 26.5′ (based on a 1″ seam)].

Available in pre-hemmed curtains 4.5' x 8' to use with a tension rod (not included) - 15 per roll.

- ► Fire Retardant to NFPA 701-2019 Test 2
- ► Made 100% in the USA
- ► Easy to clean








PRE-HEMMED

Pre-hemmed 4.5′ x 8′ curtain. Curtains are easy to glue sections together to create larger dividers.







HOW TO USE VINYL GLUE FOR WIDER WIDTH CURTAINS

In the roll stock you can create whatever length you require. You can just hang the material with a tension rod, 1/2 inch PVC pipe or rope, fold the vinyl over 4" to create a hem.

Using the vinyl glue run a bead of glue 1/2" from edge where the fold and material meet. Vinyl glue sets tacky in 2 minutes and ready for use in 1 hr. Use clear glue to get clear sight lines.





CREATE A WINDOW

Vinyl can also be used to create a window in plastic sheeting.

In the photo you see our DS2FR reinforced fire retardant 6 mil plastic with the windows and zipper openings.



EZ SQUEEZE CEILING HANGER

Attach DPC to ceiling tiles in a matter of minutes with a 6' cord in clear or black. Packed 20 or 500 per bag. (Part #: EZS*)




GROMMET SNAP

There is also a snap-on grommet you can use instead of cutting the vinyl. (Part #: TG250-20)



CLEANING VINYL

- ► Test an inconspicuous spot for vinyl safety. Wipe off with mild, soapy water.
- ► For sterilizing, use a diluted bleach solution or isopropyl alcohol; Avoid organic solvent-based and ammonia based products.
- ► Always wipe vinyl products dry before storing.



2-SIDED TAPE

Clear, 2-sided super strong bonding tape. 1.5" x 300'. (Part #: DST)







PROPERTIES

	<u> </u>	
Yield (basis weight)	-	12 mil
Color	-	Clear
Tensile Elongation	Machine Direction ASTM D882	340
Tensile Elongation	Transverse Direction ASTM D882	350
Tensile Strength	Machine Direction ASTM D882	3830
Tensile Strength	Transverse Direction ASTM D882	3460
Fire Retardancy	NFPA 701-2019 Test 2	Pass

Part Number	Description	Wgt	Size	Pallet Ct
DR12CLR91254	12 mil DPC Fire Retardant Vinyl 54" x 8' 15p/rl	53	60" x 10" x 10"	21
RS91254CLR4	12 mil DPC Fire Retardant Vinyl 54" x 400'	155	54" x 10" x 10"	10
RS91254CLR2	12 mil DPC Fire Retardant Vinyl 54" x 250'	95	60" x 7" x 7"	16
RS91254CLR1	12 mil DPC Fire Retardant Vinyl 54" x 150'	57	60" x 5" x 5"	26

NOTE: To the best of our knowledge, unless otherwise stated, these are typical property values and are intended as guides only, not as specification limits. Chemical resistance, odor transmission, longevity as well as other performance criteria is not implied or given and actual testing must be performed for applicability in specific applications and/or conditions. Americover, Inc. makes no warranties as to the fitness for a specific use or merchant ability of products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage. Limited Warranty available at www.Americover.com.







